

C-UNO2053GL-PS-ACP

Compact Single VGA ACP
ThinManager Ready Client



Features

- ThinManager Ready, ACP Enabled BIOS
- Single VGA, 1920x1200 maximum resolution
- 2x 10/100BaseT Ethernet ports
- 2x USB2.0 ports
- 2x RS-232 serial ports
- Audio line in & out, Mic in
- AC power adapter included
- Fanless design with no internal cabling for maximum reliability



Introduction

Realize the true value of thin client and centralized management technologies with Advantech's ThinManager Compatible industrial thin clients. ACP's ThinManager, the leading thin client solution for the factory floor, and Advantech's industrially hardened thin client hardware provide a unique solutions for centralized management of factory floor applications. The C-UNO2053GL-PS-ACP is the perfect ThinManager Ready industrial thin client for applications where the space saving, compact size is needed.

Specifications

General

- **Certification** CE, UL, CCC, FCC
- **Dimensions (WxDxH)** 188.8x106.5x35.5mm
- **Enclosure** Aluminum
- **Mounting** DIN-Rail, Panel Mount
- **Power Consumption** 9 ~ 36 VDC
24VDC @ 1A (15W typical)
AC adapter included
- **Weight** 0.8kg

System Hardware

- **CPU** AMD Geode LX800 500MHz
- **Memory** 256MB DDR SDRAM
- **Indicators** LEDs for Power, LAN
- **Display** Single VGA, DB15
1920x1200 max resolution
- **Audio** Line in, Line out, Mic in

I/O Interface

- **Serial Ports** 2x RS-232, 2x RS-232/422/485, DB9 ports
- **LAN** 2x 10/100Base-T, RJ45 ports
- **USB** 2x USB2.0 ports
- **Keyboard/Mouse** 1x PS/2 port

Environment

- **Humidity** 95% @40°C (non-condensing)
- **Operating Temp** -10~55°C (14~131°F)
- **Shock Protection** IEC 68 2-27
50 G @ wallmount, half sine, 11 ms
- **Vibration Protection** IEC 68 2-6
Random 1 Oct./min, 1hr/axis
2 Grms @ 5~500 Hz

Ordering Information

- **C-UNO2053GL-PS-ACP** Compact Single VGA ACP
ThinManager Ready Client
(includes AC power adapter)