

Your trusted eSurveillance Solution Partner

The IP Security Solutions

2 Megapixel Mini Bullet IP Camera

SIU5130

Triple stream
True day/night
3GPP



- 2M High image quality
- H.264 / MPEG4 / MJPEG recording
- Triple stream simultaneously
- Built-in digital motion detection
- 3GPP Mobile surveillance support
- Digital remote Pan/Tilt control when zoom in
- iPhone APP and Android APP

Product Overview

After SMAX Bullet type IP camera SIU7100 series hot sale in 2012, based on the similar product concept, SIU5130 has been developed with the similar ID design as SIU7100 to fulfill the new request feedback from customers. Equipped board lens, SIU5130 uses H.264/MPEG4/MJEP compression technologies and provides 2 megapixels image resolution at 10 frames per second. It supports several key functions like true day/night, multi stream and three scalable motion detection windows. Of course, it is free bundled 64 channel management software and free downloads APP for iPhone and Android mobile phone.

The hardware of SIU5130 is function extendable for POE, SD/Micro SD card storage interface and DI/DO for audio/video transition; even wireless connection is also available. We accept the considerable large amount request to add the optional functions on the OEM/ODM case. Please contact our sales for the details.

Specifications

Model No.		SIU5130
Product Description		2MP Outdoor H.264 Day / Night IP Bullet Camera
System	Special Features	DSP Base
CMOS Image Sensor	Format	1/2.5"
	Effective Pixels	1920H x 1080V
	Pixel size	2.2 x 2.2µm
	Active Image Area	5.70mm(H) x 4.28 mm(V), 7.13mm (diagonal)
Built-in Lens	Lens Mount	Board, M12 x P0.5
	Focal Length	4.0 mm
	F No.	F2.0
	Auto-IRIS	NA
Day/Night	Angle of View	80° (Digonal)
	Mechanical IRCF	Yes, on sensor board
Video Codec	IR Wave Length/ IR Distance	850nm / up to 15M, 5phy x 18pcs
	H.264	10fps @ 1920 x 1080 30fps @ 1200 x 960; 1280 x 720; 720 x 480; 640 x 480; 320 x 240
	MPEG4	10fps @ 1920 x 1080 30fps @ 1200 x 960; 1280 x 720; 720 x 480; 640 x 480; 320 x 240
Audio Codec	MJPEG	30fps @ 1280 x 720; 720 x 480; 640 x 480; 320 x 240
	Audio Codec	G.711 µ-law
Codec Quality Options		H.264: 5 Levels or Bit Rate; MPEG4/MJPEG: 5 Levels
Interface	Network	10Base/100Base- / RJ45
	LED Indicators	Power & Ethernet (1/1)
	Reset	Yes, On PCB board
Power Supply	PoE	NA
	AC-DC Power	DC 5V
Special Features	Motion Detection	Yes, 3 scalable windows
	Image Settings	Brightness, Contrast, Sharpness, Saturation Adjustable
	Alarm Buffer	5 Sec. pre-alarm / 5 Sec. post-alarm, up to 3MByte
	Mirror	Vertical / Horizontal
	ONVIF	Yes
	PTZ Control	Digital zoom up to 10x ; Digital Pan / Tilt
	3GPP Supported	Yes
	Packet Management	IP Filer, QOS
	Time Management	Manual Time Setting, Time Server & NTP Support, Real Time Clock
	Multi-level User Access	Yes
Environment	Multiple Streaming	Yes
	Operating Temp. / Humidity	0°C~50°C (32°F ~ 122°F), 20%~85% RH
	Storage Temp.	-20 ~ 60°C
Protocols	Weather Proof	IP65
	Protocols	TCP/IP, IPv4, IPv6, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, HTTPS, Samba, PPPoE, UPnP, Bonjour, RTP, RTSP, RTCP
Mechanical	Dimensions	ø 73 mm x 112 mm
	Material	Metal
	Accessory	1 x User Manual / ExpressView CD ROM 1 x Quick Installation Guide Bracket
Certificate		CE , FCC

