

3 Megapixel Box IP Camera

SIB7137

Day & Night, 3 Megapixel
H.264 MPEG4/MJPEG
2-way Audio Network Camera



- WDR support
- Built-in H.264, MPEG-4 and MJPEG digital signal output.
- Offers true day/night function.
- Up to QXGA resolution at 20 FPS.
- H.264 HP, MP, BP/MPEG4 SP /MJPEG multiple stream output for simultaneously live monitoring and high resolution recording.
- DC 12V or Power over Ethernet (PoE) IEEE 802.3af.
- Built-in network interface (10Base-T/100Base-TX) for remote monitoring by PC.
- Built-in SD/SDHC memory card slot for local storage.
- Built-in digital Motion Detection.
- Two way audio.
- 3GPP Mobile Surveillance supported.
- Support RS-485 communication.
- ONVIF compliant

Product Overview

The Box series IP cameras serve as the highest image quality surveillance with remarkable bandwidth efficiency. With internal built-in WDR (wide Dynamic Range), SIB7137 can support true surveillance video performance. Supporting triple stream, users can access the camera to monitor the scenes via any type of Internet gadget such as PC, PAD, POD, and mobile phone. Box series IP cameras offer true day/night function to maintain clear images 24 hours a day. The build-in SD/SDHC card slot provides a convenient and portable storage option for local storage of event and schedule recordings in case of network disconnection.

Equipped with PoE (Power over Ethernet), the Box IP camera allows power and signals to be transmitted over the same cable simultaneously. It eliminates the need of the traditional power source for each camera. The digital motion detector feature transmits an alarm signal when moving subjects enter the scene. Working with free bundle 64-CH management software, this camera supports live view and recording. The camera is ideal for high performance and an endless variety of networked surveillance applications.

Description	3Mega pixel Network Camera
IR-LED	NA
sensor	1/3" 3 Mega pixel Color CMOS sensor
Processor	DSP Base
Lens	CS mount Lens
Video Compression	H.264 HP/MP/BP, MPEG-4 SP, M-JPEG
Resolution	QXGA (2048 x1536): 20 fps, 1080p (1920 x 1080): 30 fps, 960p (1280 x 960): 30 fps, 720p (1280 x 720): 30 fps, D1(720x480):30fps, VGA (640 x 480): 30 fps, QVGA (320 x 240): 30 fps
Multiple Streaming	Yes
ICR	Yes
WDR	Yes
SD/SDHC interface	Yes
Power-over-Ethernet (IEEE 802.3af)	Yes
Audio Support	Two-way
Alarm Input/output	2x D/I, 1x D/O
Digital zoom	10x
ONVIF	Yes
Protocol	TCP/IP,IPV6,UDP,ICMP ,DHCP ,NTP ,DNS ,DDNS ,SMTP ,FTP ,HTTP ,HTTPS ,Samba,PPPoE ,UPnP, Bonjour, RTP, RTSP, RTCP,IPV4
QoS	Yes
Multi-level user access	Yes
IP filtering	Yes
3GPP support	Yes
Time Management	Manual Time Setting, Real Time Clock Time Server and NTP support
Event Management	Events Triggered by Motion detection or GPIO Image or Video Upload/Send over email ,FTP, samba Recording Video file to SD Card by schedule
System Management	64-ch Management Software(ExpressView)
Operation Temperature	0~50°C
Approvals	CE, FCC
Dimension	130 mm (D) x 72 mm (W) x 58 mm (H)
Weight	400 g
Package	Accessories: Power Supply ; Packaging(white box) ; CD